

LOMOND

code	width over flange mm	height over flange mm	projection mm	tappings wall to centre mm	width c/c vertical tubes mm	tappings face to face mm	tappings floor to centre mm	pipe centres for valves mm	outputs to EN442	
									Btu/hr Δ 50°C	watts Δ 50°C
B25/1	540	1566	140	114	457	397	110	297*	662	194
B25/2	693	1566	140	114	610	550	110	450*	853	250
B25/3	845	1566	140	114	762	702	110	602*	1037	304

Dual fuel factory fitted. Tube size: 31.75mm. Floor mounted, integral wall stays, 3/4" internal tappings. Suitable for any hot water system.
*Using MYSON valves.



LUENA

code	width mm	height mm	projection mm	tappings c/c mm	outputs to EN442	
					Btu/hr Δ 50°C	watts Δ 50°C
NOC1	600	1220	86-98	50	904	265
NOC2	600	1790	86-98	50	1723	505

Dual fuel factory fitted. Wall fixed 1/2" tappings to left side. Suitable for any hot water system.



LULONGA

code	width over flange mm	height over flange mm	width c/c vertical tubes mm	tappings face to face mm	tappings floor to centre mm	pipe centres for valves mm	outputs to EN442	
							Btu/hr Δ 50°C	watts Δ 50°C
S1/1	686	927	610	550	110	450*	548	161**
S1/2	838	927	762	702	110	602*	606	178**
S1/3	990	927	914	854	110	754*	659	193**
S1/4	693	930	610	540	110	440*	659	193**
S1/5	845	930	762	692	110	592*	727	213**
S1/6	997	930	914	844	110	744*	791	232**

Dual fuel factory fitted. Overall projection: dependent upon wall stays. Wall to centre of tapping: dependent upon wall stays.
Tube size: S1/1 to S1/3 = 25.4mm; S1/4 to S1/6 = 31.75mm.
Floor mounted, wall stays optional extra, 3/4" internal tappings. Suitable for any hot water system.
*Using MYSON valves. **Approx outputs - NPD.



MADRIGAL

code	width mm	height mm	projection mm	tappings c/c mm	outputs to EN442	
					Btu/hr Δ 50°C	watts Δ 50°C
MAD1	500	1200	103-113	150	3050	894
MAD2	600	1200	103-113	150	3661	1073
MAD3	500	1800	103-113	150	4511	1322
MAD4	600	1800	103-113	150	5411	1586

Heater kit option MEL920. Towel rail protrudes 45mm.
Wall fixed, 1/2" tappings. Closed circuit applications only.



MARANO

code	width mm	height mm	projection mm	tappings c/c mm	outputs to EN442	
					Btu/hr Δ 50°C	watts Δ 50°C
CHO1	600	1130	114-124	50	2242	657
CHO2	600	1430	114-124	50	2893	848

Heater kit option ECO450. Wall fixed, 1/2" tappings. Closed circuit applications only.

