

NAVAJO

code	width mm	height mm	projection mm	tappings wall to centre mm	width c/c vertical tube	tappings face to face mm	tappings floor to centre mm	pipe centres for valves	outputs to EN442	
									Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$
LIB1	610	610	135	120	579	N/A	N/A	579	818	240*

Dual fuel factory fitted. Wall mounted, wall fixed 1/2" tappings facing down. Suitable for any hot water system.
*Approx output - NPD.



NENE

code	width mm	height mm	projection mm	tappings c/c mm	outputs	
					Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$
NEN1	1060	580	160 - 185	870	2419	709
NEN2	1060	730	160 - 185	870	3156	925

Floor mounted, wall fitted 1/2" tappings. Suitable for any hot water system.



OPUS Vertical

code	width mm	height mm	number of tubes	projection mm	tappings face to face mm	outputs to EN442	
						Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$
MEZV1	324	2000	9	95	324*	2740	803
MEZV2	468	2000	13	95	468*	3958	1160
MEZV3	612	2000	17	95	612*	5173	1516
MEZV4	756	2000	21	95	756*	6391	1873

Wall fixed, 1/2" tappings. Closed circuit applications only.
*Downward tapping c/c = -70mm.



OPUS Horizontal

code	width mm	height mm	number of tubes	projection mm	tappings face to face mm	outputs to EN442	
						Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$
MEZH1	600	468	13	95	550	1375	403
MEZH2	600	612	17	95	550	1761	516
MEZH3	1000	468	13	95	950	2293	672
MEZH4	1000	612	17	95	950	2934	860

Wall fixed, 1/2" tappings. Closed circuit applications only.



OUSE

code	width over flange mm	height over flange mm	projection mm	tappings wall to centre mm	width c/c vertical tubes mm	tappings face to face mm	tappings floor to centre mm	pipe centres for valves mm	outputs to EN442		radiator h x w mm
									Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$	
RPW1	627	927	190	114	586	529	110	436*	989	290	390 x 441
RPW2	780	927	190	114	739	682	110	589*	1227	359	390 x 594
RPW3	881	927	190	114	840	783	110	690*	1464	429	390 x 695
RPW4	627	927	190	114	586	529	110	436*	1183	347	525 x 441
RPW5	780	927	190	114	739	682	110	589*	1467	430	525 x 594
RPW6	881	927	190	114	840	783	110	690*	1750	513	525 x 695

Tube size: 25.4mm. Floor mounted, wall fixed, 3/4" internal tappings. Closed circuit applications only.
*Using MYSON valves.



PARRETT

code	width mm	height mm	projection mm	tappings c/c mm	outputs	
					Btu/hr $\Delta 50^{\circ}\text{C}$	watts $\Delta 50^{\circ}\text{C}$
PAR1	190	1810	N/A	75	1447	424

Floor mounted, 1/2" tappings. Suitable for any hot water system.

