


KARE

ALL MEASUREMENTS ARE IN MILLIMETRES


MANUFACTURED FROM STAINLESS STEEL









Top View





6

Plumbing Position:



Vertical mount All Dimensions are in mm Max.Working Pressure: 10 Bar Max.Working Temperature: 95° C Inlet / Outlet : 1/2″ BSP Fuel : E/H/D

Note: Dimension (S1,S2) available for minumum 24 profiles Manufacturing Tolerance : - 5 mm

PRODUCT CODE	Height H mm	Length L mm	Depth D mm	Pipe Centres C-C1 mm	Bracket Centres		
					F	S	M
KRL10-7660	760	490	70	300-566	688	450	450
KRL12-7660	760	590	70	400-666	688	550	550
KR L14-7660	760	690	70	500-766	688	650	650
KRL16-7660	760	790	70	600-866	688	750	750
KRL20-7660	760	990	70	800-1066	688	950	950
KRL24-7660	760	1190	70	1000-1266	688	600-550	1150
KRL28-7660	760	1390	70	1200-1466	688	700-650	1350
KRL32-7660	760	1590	70	1400-1666	688	800-750	1550
KRL36-7660	760	1790	70	1600-1866	688	900-850	1750

FR.71-Rev.00



Technical specifications are subject to change without prior notice.

AEON is the designer heating division of Pitacs Limited. Pitacs Limited, Bradbourne Point, Bradbourne Drive, Tilbrook, Milton Keynes, Buckinghamshire, MK7 8AT, UK